Claims

The claimed invention is:

- 1. A video display device comprising:
- a display configured to display a primary image and a
- 3 picture-in-picture image (PIP) overlaying the primary image;
- 4 a processor operatively coupled to the display and
- 5 configured to receive a first video data stream for the primary
- 6 image, to receive a second video data stream for the PIP, and to
- change a PIP display characteristic in response to a
 - characteristic present/in the primary image.
 - 2. The video display device of Claim 1, wherein the PIP display characteristic is at least one of a position of the PIP on the display, a display size of the PIP, and a transparency of the PIP.
- 1 3. The video display device of Claim 1, wherein processor is
- 2 configured to analyze at least one frame of the first video data
- 3 stream and defect at least one of a continuous color portion and
- 4 a continuous texture portion on the at least one frame as the
- 5 characteristic present in the primary image.

-2

ľŲ

- 1 4. The video display device of Claim 1, wherein processor is
- 2 configured to analyze at least one frame of the first video data
- 3 stream and determine whether there is a person/image on the at
- 4 least one frame as the characteristic present in the primary
- 5 image.

J

- The video display device of Claim 1, wherein processor is configured to analyze at least one frame of the first video data stream and determine whether there is a person image on the at least one frame and at least one of a continuous color portion and a continuous texture portion as the characteristic present in the primary image.
 - 6. The video display device of Claim 1, wherein processor is configured to analyze at least one frame of the first video data stream and determine a behavior present on the at least one frame as the characteristic present in the primary image.
- 1 7. The video display device of Claim 1, wherein the PIP
- 2 display characteristic is a position of the PIP and wherein the
- 3 processor is configured to reposition the PIP to minimize
- 4 overlaying a portion of the primary image wherein the
- 5 characteristic is present in the primary image.

- 1 8. The video display device of Claim 1, wherein the PIP
- 2 display characteristic is a size of the PIP and wherein the
- 3 processor is configured to resize the PIP to minimize overlaying
- 4 a portion of the primary image wherein the characteristic is
- 5 present in the primary image.
 - 9. The video display device of Claim 1, wherein the PIP display characteristic is a transparency of the PIP and wherein the processor is configured to render the PIP transparent to transparently overlay a portion of the primary image wherein the characteristic is present in the primary image.
 - 10. The video display device of Claim 1, wherein the PIP display characteristic is a size and a position of the PIP and wherein the processor is configured to determine the size and the position of the PIP to minimize overlaying a portion of the primary image wherein the characteristic is present in the primary image.

3:

1 11. The video display device of Claim 1, wherein the video 2 display device is a television.